

610.04

45 **(H) Joints.** Provide weakened-plane joints at score lines. Form
46 weakened-plane joints to minimum depth of 1/4 slab thickness and
47 approximate 1/8-inch width using scoring tool, saw, or other means accepted
48 by the Engineer. Match curb or pavement joints. Where driveways are more
49 than 7 feet wide, provide longitudinal, weakened-plane joints.

50
51 **(I) Curing.** Cure concrete for at least 72 hours in accordance with
52 Subsection 503.03(L) – Curing Methods. Provide barricades to protect
53 concrete from pedestrian and all vehicular traffic for 48 hours, and from
54 vehicular traffic other than passenger vehicles, for 10 days.

55
56 **610.04 Measurement.** Reinforced concrete driveways will be paid on a lump
57 sum basis. Measurement for payment will not apply.

58
59 **610.05 Payment.** The Engineer will pay for accepted reinforced concrete
60 driveways on a contract lump sum basis. Payment will be full compensation for the
61 work prescribed in this section and contract documents.

62
63 The Engineer will pay for following pay item when included in proposal
64 schedule:

Pay Item	Pay Unit
(___ - Inch) Reinforced Concrete Driveway	Lump Sum

65
66
67
68
69
70 The Engineer will pay for precast concrete drop curb and driveway curb, or
71 cast-in-place integral curb and gutter under Section 638 - Portland Cement Concrete
72 Curb and Gutter.

73
74 The Engineer will pay for excavation of unsuitable material and backfill
75 with material acceptable to the Engineer under Section 203 – Excavation and
76 Embankment. If no pay item exists, refer to Subsection 104.02 – Changes.

77
78
79

END OF SECTION 610