

## SECTION 310 - BROOMING OFF

**310.01 Description.** This work includes cleaning an existing surface or a pavement according to the contract. \*|  
\*|

**310.02 Materials.** None specified.

**310.03 Construction Requirements.** The Contractor shall remove earth, dust or other foreign material and existing raised pavement markers from the entire area in question. The Contractor shall remove ravelled materials from pockets in the surface. The Contractor shall remove grass or other growth from edges of the area. The Contractor shall crop the adjacent growth closely to prevent interference with subsequent operations. The Contractor shall dispose of debris resulting from the cleaning operations. \*|  
\*|  
\*|  
\*|  
\*|  
\*|

The Contractor shall clean the edges of the existing surface so that they the Contractor may reconstruct to their original thickness and width. \*|  
\*|

The Contractor shall remove loose material and excess dust by mechanically operated broom or air pressure, supplemented by hand brooming where required. The Contractor shall apply air pressure through pipe nozzles operating from a compressor producing one hundred (100) pounds per square inch pressure. The Contractor shall do this work while the surface is thoroughly dry. \*|  
\*|  
\*|  
\*|  
\*|

**310.04 Method of Measurement.** The Engineer will not measure brooming off for payment. \*|  
|

**310.05 Basis of Payment.** The Engineer will not pay for brooming off separately. The Engineer will consider them incidental to the various contract items. \*|  
\*|  
\*|