

SECTION 612 - GROUTED RUBBLE PAVING

612.01 Description. This work includes constructing grouted rubble paving according to the contract. *

612.02 Materials.

(A) Stones. The paving stones shall be clean, sound, durable, and accepted. The stones: *

(1) may be of variable sizes, *

(2) shall not be thicker than the depth of the course that the Contractor will place and *

(3) shall average at least one-eighth (1/8) cubic foot in volume. *

(B) Grout. The grout includes one (1) part portland cement to three (3) parts of fine aggregate by volume. |

Other materials shall conform to the following: |

Portland Cement	701.01
Fine Aggregate for Concrete	703.01
Water	712.01

612.03 Construction Requirements. The Contractor shall compact the bed thoroughly and finish to a smooth surface to a depth that the surface shall be at the planned grade. The Contractor shall remove and replace soft and yielding material with material to form a stable bed according to the contract. *

The Contractor shall wet the rocks thoroughly before laying. The experience workers shall lay the rocks in full bed of grout having a stiff consistency. The Contractor shall use selected stones and shape roughly to make close joints. The Contractor shall bed the stones well in grout and form a uniform surface with broken joints. Within twenty-four (24) hours after the Contractor places the stones, the Contractor shall point the joints with grout so that the Contractor recesses the joints quarter (1/4) inch. Mortar shall not be visible on exposed rock surface. The texture of recessed pointing shall match the texture of the rock used. The Contractor shall not give pointing a smooth finish. The Contractor shall keep the paving wet while the Contractor points. *

612.04 Method of Measurement. The Engineer will measure grouted rubble paving by the cubic yard or square yard. *

The Engineer will make computation from the dimensions shown in the contract or ordered. *

612.05

612.05 Basis of Payment. The Engineer will pay for the accepted quantities *|
of grouted rubble paving at the contract unit price per cubic yard or square *|
yard as specified in the proposal. |

The price shall be full compensation for excavating, backfilling, *|
grouting, furnishing labors, materials, equipment, tools, and other *|
incidentals necessary to complete the work. *

The Engineer will make payment under: *

Pay Item	Pay Unit
Grouted Rubble Paving	Cubic Yard
Grouted Rubble Paving	Square Yard